



WELLE

CUSTOM ELECTRICAL INSULATION

HEAT SHRINK BUSBAR SLEEVE

Technical data sheet - 1kV busbar heat shrink protection sleeve

SINCE 2017

ISO 9001

OEM / ODM

Well Electric - WELLELE

No. 196 Yingchun Road, Suzhou, Jiangsu, China

Tel +86 512 6708 1529 - sale@wellele.com - www.wellele.com

热收缩连续母排保护套管 Heat Shrinkable Continuous Busbar Protection Casing

使用说明 Directions for use

- ① 起始收缩温度70℃，全部回缩温度≤125℃。由于母排管均较厚，在120℃以下加热收缩太慢，建议客户使用时用热风枪均匀加热收缩或在120℃以上烘箱内加热收缩；

② 适用温度范围：-40~125℃；

③ 使用率≤10%；

④ 环保热收缩母排保护套管产品均符合欧盟RoHS指令。
- ① The initial shrinkage temperature to 70℃, all bounce back temperature 125℃ or less. Due to the busbar tube are thicker, under 120℃ heat shrink too slow, suggest customers to use when use hot Air pressure gun uniform heating or above 120℃ oven heating contraction;

② The applicable temperature range: -40~125℃;

③ Utilization of 10% or less;

④ Environmental protection heat-shrinkable busbar protection casing products comply with the eu RoHS directive.

产品颜色 Product color

铁红、黄、绿、黑色，可按客户要求生产其他颜色。
Iron oxide red, yellow, green, black, other colors can produce according to customer's request.

10KV热缩连续母排保护套管产品的规格尺寸（10KV WMPG系列）
10 kv busbar protection casing for heat shrinkable products specification size (10 kv WMPG series)

型号	使用母排宽度	内径 (mm)	壁厚 (mm)(S)	内径 (mm)	壁厚 (mm)(L)	标准包装 (米/盘)
10KV WMPG 15/6	12/15	15±0.8	1.0±0.2	≤6	2.5±0.2	25
10KV WMPG 20/8	20/15	20±0.8	1.0±0.2	≤8	2.5±0.2	25
10KV WMPG 25/10	25/18	25±0.8	1.0±0.2	≤10	2.5±0.2	25
10KV WMPG 30/12	30/20	30±0.8	1.0±0.2	≤12	2.5±0.2	25
10KV WMPG 40/16	40/30	40±1.0	1.2±0.2	≤16	2.8±0.3	25
10KV WMPG 50/20	50/35	50±2.0	1.2±0.2	≤20	2.8±0.3	25
10KV WMPG 60/24	60/45	60±3.0	1.2±0.2	≤24	2.8±0.3	25
10KV WMPG 65/26*	65/45	65±3.0	1.2±0.3	≤26	2.8±0.3	25
10KV WMPG 70/28	70/50	70±3.0	1.2±0.3	≤28	2.8±0.3	25
10KV WMPG 75/30*	75/50	75±3.0	1.2±0.3	≤30	2.8±0.3	25
10KV WMPG 80/32	80/55	80±3.0	1.2±0.3	≤32	2.8±0.3	25
10KV WMPG 85/34*	80/65	85±3.0	1.2±0.3	≤34	2.8±0.3	25
10KV WMPG 100/40	100/75	100±4.0	1.2±0.3	≤40	2.8±0.3	25
10KV WMPG 120/48	120/85	120±4.0	1.2±0.3	≤48	2.8±0.3	25
10KV WMPG 150/60	150/105	150±4.0	1.2±0.3	≤60	2.8±0.3	25
10KV WMPG 160/64*	150/	160±4.0	1.2±0.3	≤64	2.8±0.3	25
10KV WMPG 180/72	180/120	180±5.0	1.2±0.3	≤72	2.8±0.3	25
10KV WMPG 210/84*	210/140	210±5.0	1.2±0.3	≤84	2.8±0.3	25
10KV WMPG 230/92*	230/150	230±5.0	1.2±0.3	≤92	2.8±0.3	25

说明：1、适用母线规格中20/15表示适用于20MM宽的矩形母线或直径为15MM的圆形母线。
2、带*号的规格上做库存，需要下单特殊定做。
Description: 1、suitable bus specification applies to 20 mm wide for the 20/15 in rectangle busbar or 15 mm diameter circular bus.
2、* on the specifications of the inventory, need special customized orders.



35KV热缩连续母排保护套管产品的规格尺寸（35KV WMPG系列）
35 kv busbar protection casing for heat shrinkable products specification size (35 kv WMPG series)

型号	使用母排宽度	内径 (mm)	壁厚 (mm)(S)	内径 (mm)	壁厚 (mm)(L)	标准包装 (米/盘)
35KV WMPG 30/15	30	30±1.0	1.9±0.5	15	4.0±0.3	15
35KV WMPG 35/18	30/40	35±1.0	1.9±0.5	18	4.0±0.3	15
35KV WMPG 40/20	40	40±1.0	1.9±0.5	20	4.0±0.3	15
35KV WMPG 50/25	50	50±2.0	1.9±0.5	25	4.0±0.3	15
35KV WMPG 60/30	60	60±2.0	1.9±0.5	30	4.0±0.3	15
35KV WMPG 65*/33	60/70	65±2.0	1.9±0.5	33	4.0±0.3	15
35KV WMPG 80/35	70	70±2.0	1.9±0.5	35	4.0±0.3	15
35KV WMPG 86/38*	70/80	75±2.0	1.9±0.5	38	4.0±0.3	15
35KV WMPG 90/40	80/100	80±3.0	1.9±0.5	40	4.0±0.3	15
35KV WMPG 200/50	100/120	100±4.0	1.9±0.5	50	4.0±0.3	15
35KV WMPG 120/60	150	120±4.0	1.9±0.5	60	4.0±0.3	15
35KV WMPG 150/75	180	150±4.0	1.9±0.5	75	4.0±0.3	15
35KV WMPG 180/90*	MAX	185±4.0	1.9±0.5	90	4.0±0.3	15
35KV WMPG 210/105*	MAX	210±4.0	1.9±0.5	105	4.0±0.3	15
35KV WMPG 230/115*	MAX	230±4.0	1.9±0.5	115	4.0±0.3	15

说明：带*号的规格上做库存，需要下单特殊定做。
Description: with * on the specifications of the inventory, need special customized orders.

● 特殊尺寸可订制 Special size can be customized