



CUSTOM ELECTRICAL INSULATION

Technical data sheet - vulcanized fiber and epoxy roll combination tube

SINCE 2017

ISO 9001

OEM / ODM

Well Electric - WELLELE

No. 196 Yingchun Road, Suzhou, Jiangsu, China

Tel +86 512 6708 1529 - sale@wellele.com - www.wellele.com

Vulcanized fiber and Epoxy Fiberglass Roll Combination Tube

category		parameter	
Temperature resistance		100℃	
Product appearance color		Varnish, gray UV paint, other colors can be customized	
Inner diameter range		6~20mm (Can be customized)	
Surface finish		Can be processed according to customer needs	
mechanical strength		high	
Performance test data			
Serial number	Test item		Company Requirement
1	density		g/cm3 ≥1.70
2	Water absorption		% ≤6
3	Shear strength		Mpa ≥80
4	Bending strength		Mpa ≥160
5	compressive strength		Mpa ≥90
6	Vertical resistance voltage (Normal 5min)		KV 42
	wall thickness	2.0	KV 14
	Cm	2.5	KV 16



TEL:+86-512-67081529 FAX:+86-512-65256838
E.mail:sale@wellele.com,info@wellele.com
http://www.wellele.com,allinsulating.com,fusestube.com
Add:suli RD47.Caizhi 5-712, SUZHOU, JIANGSU

	3.0	KV	18
	4.0	KV	20
	5.0	KV	24
	6.0	KV	28
	7.0	KV	30
	8.0	KV	34

Note: the above test data for the sample test data, our company
can customize products according to customer needs.